



Isometric view1: 1

Notes:

1. Materials: N-BK7
2. Design Wavelength: 587.6nm
3. Focal Length: $f = -100.0\text{mm} \pm 1\%$
4. Back Focal Length(REF): $bf = -101.98\text{mm}$
5. Centration error: ≤ 2 arc min
6. Clear aperture: $\geq 90\%$
7. G - Fine ground surface
8. Coating: AR/AR@700~1100nm(REFER TO COATING CURVES)
9. All dimensions are in mm

Parameters			SHALOM EO w w w . shalomeo . c o m		BK7 Plano-concave D=25.4 F=-100 With AR@700~1100nm Coating					
	S1	S2								
Shape	Convex	Plano								
Radius of curvature	-51.68	Infinity								
Surface quality	40/20 S/D	40/20 S/D	Proprietary		Name	Date	Part number	Rev	Scale	
Surface Irregularity	$\lambda/4@632.8\text{nm}$	$\lambda/4@632.8\text{nm}$	The drawing is property of Hangzhou Shalom EO, any reproduction in part or as a whole without permission is prohibited.		DRAWN	YSF	07/May/20	1103-023	A	2:1
Power(P-V)	$3\lambda/2@632.8\text{nm}$	$\lambda/2@632.8\text{nm}$			APPROVAL	JT	07/May/20			
Protective chamfers	0.2mm x 45°	0.2mm x 45°								